

KR545D

Tabber

Outstanding Performance

Designed and engineered to meet the USPS specifications for self-mailers and booklets that require multiple tabs per piece, the KR545D utilizes a unique dual web applicator and innovative, patented, trailing edge tab mechanism.

**Multiple
Tabs in a
single pass!**

- Servo driven web and trailing edge kicker
- Handles large 18" diameter rolls
- Also applies labels and stamps
- Operates inline with standard addressing systems



Distributed by:



Insource Corporation

Phone: 905.709.3344

Toll Free: 1.888.709.3344

Email: Sales@insourcecorp.ca

NOTE: Guards may have been removed for clarity.
Do not operate machine without guards in place.

www.insourcecorp.ca

KR545D

Tabber

** General Specifications

Physical	English	Metric
Length	72"	182.9 cm
Width	38"	96.5 cm
Height	77"	195.6 cm
Shipping Weight	1395 lbs.	632.76 kg

Electrical Requirements

Voltage	Amp	Phase	Hz
220 VAC	50	1	50/60

Compressed Air Requirements

80 psi	at 5.0 acfm
--------	-------------

Features:

- Servo driven controls
- Side register belts for tight tabs
- Touch screen operator interface
- Side to side tabletop adjustment
- Quick-release upper belt system
- Quick-release peel plates
- Stop-in/Stop-out electrical interface
- KR conveyor pass through controls

Products

Tabs/Labels	Min. .50" dia. (1.27 cm)	Max 1.5" dia. (3.81 cm)
Tab Quantity	1 to 6 Tabs or STamps	
Tab Accuracy	+/- .0625" (1.6 mm)	
Labels	3" (7.62 cm) Width x 2" (5.1 cm) Length	
Materials	Minimum: 3.50" W (8.9 cm) 3.50" L (8.9 cm) .008" T (0.2 mm)	Maximum: 11" W (27.9 cm) 11" L (27.9 cm) .25" T (6.3 mm)

Operating Speeds

Maximum	350 fpm (138 mpm)
---------	-------------------

NOTE: Speeds are dependent on material being fed.

Options:

- Hydraulic lift kit for up to 5"
- Vacuum web waste removal kit
- Bump turn for infeed table section



Distributed by:



Insource Corporation

Phone: 905.709.3344

Toll Free: 1.888.709.3344

Email: Sales@insourcecorp.ca

****Specifications subject to change without notice.**

www.insourcecorp.ca